

Viton® - wt: 1.6 | id: 0.8 | od: 4 (per meter)

P/N: 525-53000-00



For Single- and Multi-Channel use (not suitable with cassette small)

- Application: Excellent acid resistance at high temperatures
- Features:
 - Low gas permeability
 - Resistant to solvents and corrosives at high temperatures
- Material: Fluorocarbon rubber, thermoformed Viton® B (67% fluorinated); opaque black
- Complies with the standards: GLP conform
- Temperature range: -30 to +205 °C
- Sterilization: Sterilization is not recommended
- Restriction: Limited performance life

Used with:

Acids:	excellent
Lyes:	excellent

Premium Laboratory Equipment

Solvents:	varies; tests recommended
Pressure:	good
Vacuum:	good
Viscous media:	good
Sterile media:	satisfactory

Viton® - wt: 1.6 | id: 0.8 | od: 4 (per meter) - Technical Data

Inner diameter	0.8 mm
Outer diameter	4 mm
Wall thickness (wt)	1.6 mm
Max. Pressure (continuous / short time)	0.7 / 1.7 bar
Suction height	8.8 mH ₂ O
SP quick Advantage 06 / Precision 06 (min/max)	2 – 33 ml/min
SP quick Value 06 (min/max)	4 – 35 ml/min
SP quick Advantage 01 / Precision 01 (min/max)	0.38 – 9 ml/min
SP quick Value 01 (min/max)	0.83 – 9 ml/min
SP standard/vario Advantage 06 / Precision 06 (min/max)	not suitable
SP standard/vario Value 06 (min/max)	not suitable
SP standard/vario Advantage 01 / Precision 01 (min/max)	not suitable
SP standard/vario Value 01 (min/max)	not suitable
Hei-FLOW Advantage 01 / Precision 01 - pump head C 12 - Cassette small (min/max)	not suitable
Hei-FLOW Advantage 01 / Precision 01 - pump head C 4 - Cassette small (min/max)	not suitable
Hei-FLOW Value 01 - pump head C 12 - Cassette small (min/max)	not suitable
Hei-FLOW Value 01 - pump head C 4 - Cassette small (min/max)	not suitable
Hei-FLOW Value 01 - pump head C 8 - Cassette medium (min/max)	0.55 – 6.97 ml/min
Hei-FLOW Value 01 - pump head C 8 - Cassette large (min/max)	not suitable
Hei-FLOW Advantage 01 / Precision 01 - pump head C 8 - Cassette medium (min/max)	0.24 – 7 ml/min

Hei-FLOW Advantage 01 / Precision 01 - pump not suitable
head C 8 - Cassette large (min/max)

Flow rates pertain to

Tygon® (standard) tubing and water