

PharMed® - wt: 1.6 | id: 6.4 | od: 9.5 (per meter)

P/N: 525-20028-00



For Single- and Multi-Channel use (not suitable with cassette small)

- Application: Ideal for medical, lab and research uses
- Features:
 - High fatigue strength under repeated reversed bending stresses
 - Non-toxic, biocompatible
 - Very low gas permeability
 - Well suited to acids and bases
- Material: Thermoplastic elastomer on a polypropylene base with plasticizers; excellent tensile strength; opaque
- Complies with the standards: USP Class VI, GLP, Pharmacopoea and Europaea
- Temperature range: -51 to +135 °C
- Sterilization: Can be autoclaved or sterilized with ethylene oxide or sterilized by irradiation
- Restriction: Additives may migrate

Used with:

Premium Laboratory Equipment

Acids:	good
Lyes:	good
Solvents:	unsuitable
Pressure:	good
Vacuum:	excellent
Viscous media:	good
Sterile media:	excellent

PharMed® - wt: 1.6 | id: 6.4 | od: 9.5 (per meter) - Technical Data

Inner diameter	6.4 mm
Outer diameter	9.5 mm
Wall thickness (wt)	1.6 mm
Max. Pressure (continuous / short time)	0.5 / 1.5 bar
Suction height	6.7 mH ₂ O
SP quick Advantage 06 / Precision 06 (min/max)	89 – 2,072 ml/min
SP quick Value 06 (min/max)	186 – 1,765 ml/min
SP quick Advantage 01 / Precision 01 (min/max)	17 – 409 ml/min
SP quick Value 01 (min/max)	36 – 413 ml/min
SP standard/vario Advantage 06 / Precision 06 (min/max)	167 – 4,056 ml/min
SP standard/vario Value 06 (min/max)	364 – 4,151 ml/min
SP standard/vario Advantage 01 / Precision 01 (min/max)	33 – 813 ml/min
SP standard/vario Value 01 (min/max)	75 – 861 ml/min
Hei-FLOW Advantage 01 / Precision 01 - pump head C 12 - Cassette small (min/max)	not suitable
Hei-FLOW Advantage 01 / Precision 01 - pump head C 4 - Cassette small (min/max)	not suitable
Hei-FLOW Value 01 - pump head C 12 - Cassette small (min/max)	not suitable
Hei-FLOW Value 01 - pump head C 4 - Cassette small (min/max)	not suitable
Hei-FLOW Value 01 - pump head C 8 - Cassette medium (min/max)	not suitable
Hei-FLOW Value 01 - pump head C 8 - Cassette large (min/max)	26 – 364 ml/min
Hei-FLOW Advantage 01 / Precision 01 - pump head C 8 - Cassette medium (min/max)	not suitable

Hei-FLOW Advantage 01 / Precision 01 - pump 11 – 329 ml/min
head C 8 - Cassette large (min/max)

Flow rates pertain to

Tygon® (Standard) tubing and water