

## Unimax 2010

P/N: 542-10020-00



The resilient one with a maximum loading capacity of 10 kg

The Unimax 2010 is the optimal model for increased sample throughput. With a usable area of 390 x 340 mm and the possibility of a multi-story structure, space is used effectively.

The orbit of 20 mm and speeds between 20 and 400 rpm guarantee gentle mixing of all samples. This shaker can be operated either continuously or with an integrated timer (max. 120 min).

## Unimax 2010 - Technical Data

Overheat protection	self-resetting
Permissible ambient conditions	5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity
Weight	16 kg
Protection class (EN 60529)	IP 20
Timer	yes (max. 120 min)
Rotation speed range	20 - 400 rpm
Power input	115
Dimensions (w/d/h)	426 x 435 x 135 mm
Max. Load	10 kg
Operating Mode	timer or continuous
Rotation speed setting	digital
Orbit / Stroke	20 mm
Platform size	390 x 340 mm
Accessories included	non-skid rubber mat
Angle	-
Motion	orbital
Ambient temperature range (operation)	-
Ambient temperature range (storage)	-
Interfaces	-
Usable area	-
Installation altitude	-