Premium Laboratory Equipment

Hei-VAP Expert - hand lift model with G5 dry ice condenser

P/N: 036041003



reddot winner 2020
interface design

DESIGN
AWARD
2021

Most
Innovative
Product
SalesConvention
LLG
AWARD
2019

Precise setting of rotation speed and heating bath temperature on the digital touch display or – for quick access during an active process – directly via the knobs on the operating panel.

- Central operating panel with 5“ touch display
- Hand lift model with G5 dry ice condenser
- Clear display of all values (Basic and Advanced modes)
- With timer, limitation of max. temperature, multilingual menu and text display for error messages
- Separate knobs for rotation and heating with locking function to prevent accidental readjusting
- LED ring lights and pictogram to display the activity even from a distance
- Integrated solvent library to facilitate adjustment of the required vacuum on an external vacuum controller
- USB and Micro SD interfaces
- Optional display of vapor temperature
- Subsequent upgrade to Hei-VAP Expert Control possible, including vacuum and chiller control

Learn about the differences between this configuration with a G3XL condenser in combination with a recirculating chiller.

Hei-VAP Expert - Technical Data

Rotation speed indicator	5" LCD color graphic display
Permissible ambient conditions	5 – 31 °C at 80 % rel. humidity 32 – 40 °C decreasing lineary up to max 50% rel. humidity
Protection class (EN 60529)	IP 20
Lift	Hand lift
Height adjustment speed	manual
Height adjustment	155 mm
Drive	brushless DC motor with electronic speed control
Heating capacity	1,300 W
Temp. range heating bath	20 – 210 °C
Temperature accuracy bath	±1K
Overheat protection bath	cut-off at 5 °C over set temperature via separate PT 1000
Bath temperature setting	5" LCD color graphic display
Heating bath temperature control	electronic / digital
Secondary overtemp. cut off	250 °C
Material heating bath	stainless steel V4A
Diameter heating bath	255 mm
Volume heating bath	Up to 6 liter (2.2 to 4.5 liter recommended filling volume, depending on the flask size and immersion angle used)
Display vapor temperature	Yes
Required accessories for display vapor temperature	Vapor temperature sensor
Integrated vacuum controller	-
Timer	Yes
Programmable ramps	Yes

Supply Power	1,400 W
Weight without glassware assembly	15 kg
Dimensions with glassware set G3 (w/d/h)	739 x 532 x 887 mm
Dimensions with glassware set G3 XL (w/d/h)	739 x 532 x 920 mm
Condensing surface	1,400 cm²
Condensing surface XL condenser	2,200 cm²
Max. size evaporating flask	5 l
Rotation speed range	10 - 280 rpm
Integrated Hei-CHILL controller	-
Vacuum program Dynamic AUTOaccurate requires AUTOaccurate sensor	-
Solvent libary	Yes