

## Reax top

P/N: 541-10000-00



The classic with 5 mm shaking orbit

This model is particularly suitable for simple mixing tasks. In short-term operation mode, the shaking motion is triggered by pressure on the test tube tray. This mode is suitable for mixing up solutions, for example.

Persistent cell pellets can be dissolved gently but powerfully in continuous operation. With a speed of up to 3,200 rpm and a shaking orbit of 5 mm, reliable and uniform distribution of solids, and homogenization of highly viscous media are guaranteed.

## Reax top - Technical Data

Overheat protection	self-resetting
Permissible ambient conditions	5 - 31 °C at 80 % rel. humidity 32 - 40 °C decreasing linearly up to max. 50 % rel. humidity
Weight	0.000 kg
Protection class (EN 60529)	IP 22
Timer	-
Rotation speed range	200 - 3,200 rpm
Power input	51
Dimensions (w/d/h)	134 x 172 x 105 mm
Max. Load	-
Operating Mode	automatic or continuous
Rotation speed setting	analog
Orbit / Stroke	0 mm
Platform size	-
Accessories included	-
Angle	-
Motion	vibrating
Ambient temperature range (operation)	-
Ambient temperature range (storage)	-
Interfaces	-
Usable area	-
Installation altitude	-