

# Hei-TORQUE Core

P/N: 501-60410-00



40Ncm

Heidolph

!

2.3Kg

, Hei-TORQUE Core

( , )  
가

가 “Core” 가

, Hei-TORQUE Core

(Quick Chuck)

2,000rpm

“Max”

Hei-TORQUE Core

10.5mm

.가

, 10,000mPas,

25

가

(H<sub>2</sub>O).

## Hei-TORQUE Core -

|                             |                     |     |          |
|-----------------------------|---------------------|-----|----------|
|                             | 105 W               |     |          |
|                             | 75 W                |     |          |
|                             | 1                   |     |          |
|                             |                     | 2   |          |
|                             |                     |     |          |
|                             | 40 Ncm              |     |          |
|                             |                     |     |          |
|                             |                     |     |          |
|                             | 10,000 mPa s        |     |          |
| (H <sub>2</sub> O), .       | 25 l                |     |          |
| /                           | -                   |     |          |
| 가                           |                     |     |          |
| /                           |                     |     |          |
| ,                           | 10.5 mm             |     |          |
| 가                           | 5~31 °C<br>50%      | 80% | 32~40 °C |
|                             | 2.3 kg              |     |          |
| Protection class (EN 60529) | IP 42               |     |          |
|                             | 20~2,000rpm         |     |          |
| ( , x l)                    | 13 x 160 mm         |     |          |
| ( / / )                     | 70 x 195 x 281.5 mm |     |          |
|                             | -                   |     |          |
| Through-                    |                     |     |          |