

- wt: 1.6 | id: 0.8 | od: 4 ()
P/N: 525-33000-00



- ()
- :
• :
 -
 -
 -
 -
 -
 - : 가 , ,
 - : USP Class VI, FDA, GLP NSF
 - : -80 +200 °C
 - : 30 가
 - : , , 가 , 가
- :

:
가 :
:
:
:
:
:
:
:
:

- wt: 1.6 | id: 0.8 | od: 4 () -

	0.8 mm
	4 mm
(wt)	1.6 mm
(/)	0.7 / 1.7 bar
	8.8 mH ₂ O
SP quick Advantage 06/Precision 06(/)	2 – 33 ml/min
SP quick Value 06(/)	4 – 35 ml/min
SP quick Advantage 01/Precision 01(/)	0.38 – 9 ml/min
SP quick Value 01(/)	0.83 – 9 ml/min
SP standard/Advantage 06/Precision 06(/)	not suitable
SP standard/Value 06(/)	not suitable
SP standard/Advantage 01/Precision 01(/)	not suitable
SP standard/Value 01(/)	not suitable
Hei-FLOW Advantage 01/Precision 01 - C12 - (/)	not suitable
Hei-FLOW Advantage 01/Precision 01 - C4 - (/)	not suitable
Hei-FLOW Value 01 - C12 - (/)	not suitable
Hei-FLOW Value 01 - C4 - (/)	not suitable
Hei-FLOW Value 01 - C8 - (/)	0.55 – 6.97 ml/min
Hei-FLOW Value 01 - C8 - (/)	not suitable
Hei-FLOW Advantage 01/Precision 01 - C8 - (/)	0.24 – 7 ml/min

Hei-FLOW Advantage 01/Precision 01 - C8 - (/)	not suitable
	Tygon® (standard) tubing and water