

- wt: 0.9 | id: 1.42 | od: 3.22

P/N: 525-30015-00



(40 cm)

- :
• :
 -
 - ,
 - ,
 - ,
- : 가 , ,
- : USP Class VI, FDA, GLP NSF
- : -80 +200 °C
- : 30 가
- : , , 가 , 가
- :

:
가 :
:
:
:
:
:
:
:
:

- wt: 0.9 | id: 1.42 | od: 3.22 -

	1.42 mm
	3.22 mm
(wt)	0.9 mm
(/)	0.5 / 1.5 bar
	7 mH ₂ O
SP quick Advantage 06/Precision 06(/)	not suitable
SP quick Value 06(/)	not suitable
SP quick Advantage 01/Precision 01(/)	not suitable
SP quick Value 01(/)	not suitable
SP standard/Advantage 06/Precision 06(/)	not suitable
SP standard/Value 06(/)	not suitable
SP standard/Advantage 01/Precision 01(/)	not suitable
SP standard/Value 01(/)	not suitable
Hei-FLOW Advantage 01/Precision 01 - C12 - (/)	0.10 – 3 ml/min
Hei-FLOW Advantage 01/Precision 01 - C4 - (/)	0.60 – 14 ml/min
Hei-FLOW Value 01 - C12 - (/)	0.23 – 3 ml/min
Hei-FLOW Value 01 - C4 - (/)	1 – 15 ml/min
Hei-FLOW Value 01 - C8 - (/)	not suitable
Hei-FLOW Value 01 - C8 - (/)	not suitable
Hei-FLOW Advantage 01/Precision 01 -	not suitable

C8 -	(/)	
Hei-FLOW Advantage 01/Precision 01 -		not suitable
C8 -	(/)	
		Tygon® (Standard) tubing and water