

Viton®

- wt: 0.9 | id: 1.42 | od: 3.22

P/N: 525-50015-00



(40 cm)

- :
- :
 - 가
 -
- : , Viton® B (67%);
- : GLP
- : -30 +205 ° C
- : 16 +250 ° C
- :

:

:

가 :

•

■

■

■

Viton®

- wt: 0.9 | id: 1.42 | od: 3.22 -

	1.42 mm
	3.22 mm
(wt)	0.9 mm
(/)	0.5 / 1.5 bar
	7 mH ₂ O
SP quick Advantage 06/Precision 06(/)	not suitable
SP quick Value 06(/)	not suitable
SP quick Advantage 01/Precision 01(/)	not suitable
SP quick Value 01(/)	not suitable
SP standard/Advantage 06/Precision 06(/)	not suitable
SP standard/Value 06(/)	not suitable
SP standard/Advantage 01/Precision 01(/)	not suitable
SP standard/Value 01(/)	not suitable
Hei-FLOW Advantage 01/Precision 01 - C12 - (/)	0.10 – 3 ml/min
Hei-FLOW Advantage 01/Precision 01 - C4 - (/)	0.60 – 14 ml/min
Hei-FLOW Value 01 - C12 - (/)	0.23 – 3 ml/min
Hei-FLOW Value 01 - C4 - (/)	1 – 15 ml/min
Hei-FLOW Value 01 - C8 - (/)	not suitable
Hei-FLOW Value 01 - C8 - (/)	not suitable

Hei-FLOW Advantage 01/Precision 01 - not suitable
C8 - (/)

Hei-FLOW Advantage 01/Precision 01 - not suitable
C8 - (/)

Tygon® (Standard) tubing and water