

Viton®

P/N: 525-50026-00

- wt: 0.9 | id: 2.79 | od: 4.59 ()



- :
 - :
 - 가
 -
 - : , Viton® B (67%) ;
 - : GLP
 - : -30 +205 ° C
 - : 16 +250 ° C
 - :

:

:

가 :
:
:
:
:
:
:
:
:
:

Viton®

- wt: 0.9 | id: 2.79 | od: 4.59 () -

	2.79 mm
	4.59 mm
(wt)	0.9 mm
(/)	0.5 / 1.5 bar
	7 mH ₂ O
SP quick Advantage 06/Precision 06(/)	not suitable
SP quick Value 06(/)	not suitable
SP quick Advantage 01/Precision 01(/)	not suitable
SP quick Value 01(/)	not suitable
SP standard/Advantage 06/Precision 06(/)	not suitable
SP standard/Value 06(/)	not suitable
SP standard/Advantage 01/Precision 01(/)	not suitable
SP standard/Value 01(/)	not suitable
Hei-FLOW Advantage 01/Precision 01 - C12 - (/)	0.29 – 9 ml/min
Hei-FLOW Advantage 01/Precision 01 - C4 - (/)	2 – 36 ml/min
Hei-FLOW Value 01 - C12 - (/)	0.69 – 8 ml/min
Hei-FLOW Value 01 - C4 - (/)	4 – 37 ml/min
Hei-FLOW Value 01 - C8 - (/)	not suitable
Hei-FLOW Value 01 - C8 - (/)	not suitable

Hei-FLOW Advantage 01/Precision 01 - not suitable
C8 - (/)

Hei-FLOW Advantage 01/Precision 01 - not suitable
C8 - (/)

Tygon® (Standard) tubing and water