

Tygon® standard

- wt: 0.9 | id: 0.51 | od: 2.31

P/N: 525-60013-00



(40 cm)

- :
• :
 ○ ,
 ○ ,
 ○ 가 ,
• : 가 PVC,
• : FDA(21 CFR 177.2601) GLP
• : -50 +75 °C
• : 30 120 °C ()
• : 가 가
:
:

:
가 :
:
:
:
:
:
:
:
:

Tygon® standard

- wt: 0.9 | id: 0.51 | od: 2.31 -

	0.51 mm
	2.31 mm
(wt)	0.9 mm
(/)	0.5 / 1,5 bar
	7 mH ₂ O
SP quick Advantage 06/Precision 06(/)	not suitable
SP quick Value 06(/)	not suitable
SP quick Advantage 01/Precision 01(/)	not suitable
SP quick Value 01(/)	not suitable
SP standard/Advantage 06/Precision 06(/)	not suitable
SP standard/Value 06(/)	not suitable
SP standard/Advantage 01/Precision 01(/)	not suitable
SP standard/Value 01(/)	not suitable
Hei-FLOW Advantage 01/Precision 01 - C12 - (/)	0.01 – 0.54 ml/min
Hei-FLOW Advantage 01/Precision 01 - C4 - (/)	0.08 – 2 ml/min
Hei-FLOW Value 01 - C12 - (/)	0.02 – 0.42 ml/min
Hei-FLOW Value 01 - C4 - (/)	0.17 – 2 ml/min
Hei-FLOW Value 01 - C8 - (/)	not suitable
Hei-FLOW Value 01 - C8 - (/)	not suitable

Hei-FLOW Advantage 01/Precision 01 - not suitable
C8 - (/)

Hei-FLOW Advantage 01/Precision 01 - not suitable
C8 - (/)

Tygon® (Standard) tubing and water