

# Tygon® standard

- wt: 0.9 | id: 0.89 | od: 2.69

P/N: 525-60014-00



(40 cm)

- :  
• :  
◦ ,  
◦ ,  
◦ 가 ,  
• : 가 PVC,  
• : FDA(21 CFR 177.2601) GLP  
• : -50 +75 °C  
• : 30 120° C ( )  
• : 가 가  
:

:  
가 :  
:  
:  
:  
:  
:  
:

## Tygon® standard

- wt: 0.9 | id: 0.89 | od: 2.69 -

	0.89 mm
	2.69 mm
(wt)	0.9 mm
( / )	0.5 / 1.5 bar
	7 mH <sub>2</sub> O
SP quick Advantage 06/Precision 06( / )	not suitable
SP quick Value 06( / )	not suitable
SP quick Advantage 01/Precision 01( / )	not suitable
SP quick Value 01( / )	not suitable
SP standard/Advantage 06/Precision 06( / )	not suitable
SP standard/Value 06( / )	not suitable
SP standard/Advantage 01/Precision 01( / )	not suitable
SP standard/Value 01( / )	not suitable
Hei-FLOW Advantage 01/Precision 01 - C12 - ( / )	0.03 – 1 ml/min
Hei-FLOW Advantage 01/Precision 01 - C4 - ( / )	0.24 – 6 ml/min
Hei-FLOW Value 01 - C12 - ( / )	0.10 – 1 ml/min
Hei-FLOW Value 01 - C4 - ( / )	0.57 – 6 ml/min
Hei-FLOW Value 01 - C8 - ( / )	not suitable
Hei-FLOW Value 01 - C8 - ( / )	not suitable

Hei-FLOW Advantage 01/Precision 01 - not suitable  
C8 - ( / )

Hei-FLOW Advantage 01/Precision 01 - not suitable  
C8 - ( / )

Tygon® (Standard) tubing and water