

- wt: 2.5 | id: 6.4 | od: 11.3 ()
P/N: 525-39000-00



- ()
- :
• :
 -
 -
 -
 -
 -
 - : 가 , ,
 - : USP Class VI, FDA, GLP NSF
 - : -80 +200 °C
 - : 30 가
 - : , , 가 , 가
- :

:
가 :
:
:
:
:
:
:
:
:

- wt: 2.5 | id: 6.4 | od: 11.3 () -

	6.4 mm
	11.3 mm
(wt)	2.5 mm
(/)	0.8 / 1.8 bar
	8.8 mH ₂ O
SP quick Advantage 06/Precision 06(/)	85 – 2,248 ml/min
SP quick Value 06(/)	180 – 2,411 ml/min
SP quick Advantage 01/Precision 01(/)	18 – 435 ml/min
SP quick Value 01(/)	38 – 454 ml/min
SP standard/Advantage 06/Precision 06(/)	139 – 3,821 ml/min
SP standard/Value 06(/)	313 – 3,782 ml/min
SP standard/Advantage 01/Precision 01(/)	28 – 769 ml/min
SP standard/Value 01(/)	68 – 773 ml/min
Hei-FLOW Advantage 01/Precision 01 - C12 - (/)	not suitable
Hei-FLOW Advantage 01/Precision 01 - C4 - (/)	not suitable
Hei-FLOW Value 01 - C12 - (/)	not suitable
Hei-FLOW Value 01 - C4 - (/)	not suitable
Hei-FLOW Value 01 - C8 - (/)	not suitable
Hei-FLOW Value 01 - C8 - (/)	not suitable
Hei-FLOW Advantage 01/Precision 01 - C8 - (/)	not suitable

Hei-FLOW Advantage 01/Precision 01 - C8 - (/)	not suitable
	Tygon® (Standard) tubing and water