

Viton® - wt: 2.5 | id: 7.9 | od: 12.9 ()

P/N: 525-52000-00



()

- :
• :
◦ 가
◦
- : , Viton® B (67%) ;
- : GLP
- : -30 +205 °C
- : 16 +250 °C
- :

•

가 :

•
•
•
•

,

•
•

Viton® - wt: 2.5 | id: 7.9 | od: 12.9 () -

	7.9 mm
	12.9 mm
(wt)	2.5 mm
(/)	0.8 / 1.8 bar
	8.8 mH ₂ O
SP quick Advantage 06/Precision 06(/)	113 – 3,171 ml/min
SP quick Value 06(/)	257 – 3,436 ml/min
SP quick Advantage 01/Precision 01(/)	25 – 630 ml/min
SP quick Value 01(/)	50 – 630 ml/min
SP standard/Advantage 06/Precision 06(/)	not suitable
SP standard/Value 06(/)	not suitable
SP standard/Advantage 01/Precision 01(/)	not suitable
SP standard/Value 01(/)	not suitable
Hei-FLOW Advantage 01/Precision 01 - C12 - (/)	not suitable
Hei-FLOW Advantage 01/Precision 01 - C4 - (/)	not suitable
Hei-FLOW Value 01 - C12 - (/)	not suitable
Hei-FLOW Value 01 - C4 - (/)	not suitable
Hei-FLOW Value 01 - C8 - (/)	not suitable
Hei-FLOW Value 01 - C8 - (/)	not suitable
Hei-FLOW Advantage 01/Precision 01 - C8 - (/)	not suitable

Hei-FLOW Advantage 01/Precision 01 - C8 - (/)	not suitable
	Tygon® (Standard) tubing and water