

Hei-VAP Core - G5

P/N: 571-01500-00



, 가 ,

-
- 가 가 가 2 :

- LED 가

- 155mm , 20° 80°
- 50 ° C가 가

- G5
- 가

[Learn about the differences between this configuration with a G3XL condenser in combination with a recirculating chiller.](#)

Hei-VAP Core -

	3.5" LCD Display
가	5 – 31 °C at 80 % rel. humidity 32 – 40 °C decreasing lineary up to max 50% rel. humidity
Protection class (EN 60529)	IP 20
	Hand lift
	manual
	155 mm
	brushless DC motor with electronic speed control
가	1,300 W
가	20 – 210 °C
	±1K
	cut-off at 5 °C over set temperature via separate PT 1000
	3.5" LCD Display
가	electronic / digital
2	250 °C
가	stainless steel V4A
가	255 mm
가	Up to 6 liter (2.2 to 4.5 liter recommended filling volume, depending on the flask size and immersion angle used)
	-
	-
	-
	-
가	-
	1,400 W

		15 kg
G3	(/ /)	739 x 487 x 845 mm
G3 XL	(/ /)	739 x 487 x 920 mm
		1,400 cm ²
XL		2,200 cm ²
		5 l
		10 - 280 rpm
Hei-CHILL		-
Dynamic AUTOaccurate		-
AUTOaccurate		-
		-