

Hei-VAP Core - G1
P/N: 572-01100-00



- 가 , ,
- - 가 가 가 2 :
 -
 - LED 가
 - 155mm , 20° 80°
 - 50°C가 가
 - G1 Hei-VAP Core
 - 가

Hei-VAP Core -

	3.5" LCD Display
가	5 – 31 °C at 80 % rel. humidity 32 – 40 °C decreasing lineary up to max 50% rel. humidity
Protection class (EN 60529)	IP 20
	Motor lift
	25 mm/s
	155 mm
	brushless DC motor with electronic speed control
가	1,300 W
가	20 – 210 °C
	±1K
	cut-off at 5 °C over set temperature via separate PT 1000
	3.5" LCD Display
가	electronic / digital
2	250 °C
가	stainless steel V4A
가	255 mm
가	Up to 6 liter (2.2 to 4.5 liter recommended filling volume, depending on the flask size and immersion angle used)
	-
	-
	-
	-
가	-
	1,400 W

15 kg					
G3	(	/	/	)	739 x 432 x 845 mm
G3 XL	(	/	/	)	739 x 432 x 920 mm
1,400 cm ²					
XL	2,200 cm ²				
5 l					
10 - 280 rpm					
Hei-CHILL	-				
Dynamic AUTOaccurate	-				
AUTOaccurate					
-					