

Hei-VAP Ultimate Control - G6

P/N: 576-02600-00



reddot winner 2020
interface design



DESIGN
AWARD
2021



Hei-VAP Ultimate

가

- 7"
- G6
- ,
- :
- ,
- 2
- . USB 가
- ()
- Dynamic AUTO_{accurate}(DAA) 가 :
- USB SD + LAN / RS 232 (Lab 4.0 가)

Hei-VAP Ultimate Control -

	7" LCD color graphic display
가	5 – 31 °C at 80 % rel. humidity 32 – 40 °C decreasing lineary up to max 50% rel. humidity
Protection class (EN 60529)	IP 20
	Motor lift
	25 mm/s
	155 mm
	brushless DC motor with electronic speed control
가	1,300 W
가	20 – 210 °C
	±1K
	cut-off at 5 °C over set temperature via separate PT 1000
	7" LCD color graphic display
가	electronic / digital
2	250 °C
가	stainless steel V4A
가	255 mm
가	Up to 6 liter (2.2 to 4.5 liter recommended filling volume, depending on the flask size and immersion angle used)
	Yes
	Vapor temperature sensor
	Yes
	Yes
가	Yes
	1,400 W

		15 kg
G3	(/ /)	739 x 477 x 887 mm
G3 XL	(/ /)	739 x 477 x 920 mm
		1,400 cm ²
XL		2,200 cm ²
		5 l
		10 - 280 rpm
Hei-CHILL		Yes
Dynamic AUTOaccurate		Yes
AUTOaccurate		
		Yes