

Hei-TORQUE Expert 400

P/N: 501-64010-00



With Hei-TORQUE Expert 400 you can optimally stir viscosities up to 250,000 mPas or volumes up to 100 liters (H₂O). Thanks to its 2-gear stage design, it stirs particularly powerfully in the speed range up to 400 rpm and is therefore particularly suitable for applications with highly viscous media that require mixing in the lower speed range. However, operation at speeds of up to 2,000 rpm is also possible in the second speed.

The overhead stirrer Hei-TORQUE Expert 400 performs every stirring task with minimal noise thanks to the latest engine technology. This easy-to-use overhead stirrer has a display of 2.4 inches, which makes it very easy to set the application parameters and control the process (e.g. using the torque trend display). The safety-related start/stop touch-function serves to minimize the risk of unintentional switching on.

Suitable for use in fume hoods or as a drive for reactor superstructures, the Hei-TORQUE Expert 400 has a quick-action chuck (quick chuck with safety ring) with a diameter of 10.5 mm, which can be combined with a large number of stirring tools for the best stirring results.

Hei-TORQUE Expert 400 - Teknik veri

Güç derecelendirme motor girişı	150 W
Güç derecelendirme motor çıkışı	90 W
Vitesin numarası	2
Rotasyon hız göstergesi	digital monochrom 2.4"
Hız kontrol	electronic
Tork, maksimum	400 Ncm
Tork göstergesi	symbol
Aşırı ısınma koruması	automatic cut-out
Motor koruması	temperature control software
Maks. Viskozite	250.000 mPa s
Maks. karıştırma kağasitesi (H2O)	100 l
Analog/ dijital arayüz	-
Kabul edilebilir durum	continuous operation
Sayaç/ Zamanlayıcı	-
Şaft çapı , maks.	10,5 mm
İzin verilen ortam koşulları	5 – 31 °C at 80 % rel. humidity 32 – 40 °C decreasing linearly up to max. 50 % rel. humidity
Ağırlık	5,3 kg
Protection class (EN 60529)	IP 54
Rotasyon hız derecesi	10 - 400 rpm / 20 - 2,000 rpm
Stay bar ölçüsü (dia. x l)	13 x 160 mm
Dimensions (w/d/h)	93 x 247 x 350 mm
Rotasyon yön değışimi	-
Boyunca- şaft dizayn	yes