

Hei-VAP Industrial B with glassware A1

P/N: 518-24102-00



- Universal heating bath accommodates water or other bath fluids allowing for temperature settings up to 180 °C
- Receiver cassettes protect against threat of glassware breakage
- Comes as standard with integrated refill water system, spillover prevention and a release valve at the bottom
- Optional Base Cart is fully-maneuverable with removable panels for storage of vacuum pump, glassware, solvents or accessories
- Certification according to GMP available for this model: validation for installation (IQ) and operating qualification (OQ)
- Large touch screen control panel with illuminated displays for all process parameters, programmable ramps

Features identical specifications as the Hei-VAP Industrial, but for limited budgets and comes without these safety aspects:

- Metal frame and safety glass guard hood covering the bath
- High-impact PMMA door covering the glassware assembly
- High-impact PMMA latching doors which cover the receiving flask cassettes

Hei-VAP Industrial B model with glassware A1 - For low-boiling solvents and highest recovery rates

This glassware assembly includes one ascending, one descending condenser, one ascent pipe, one 20-l evaporating flask and one 10-l receiving flask

Hei-VAP Industrial B - Technical Data

Rotasyon hız göstergesi	digital
İzin verilen ortam koşulları	5 – 31 °C at 80 % rel. humidity 32 – 40 °C decreasing lineary up to max 50% rel. humidity
Protection class (EN 60529)	IP 20
Asansör	motor lift
Yüksek hız ayarı	45 mm/s
Yüksek ayar	180 mm
Sürüş	EC-motor
Isıtma kapasitesi	4.000 W
Sıcaklık derecesi ısıtma banyosu	20 – 180 °C
Banyo sıcaklık ayarı	digital
Isıtma banyo materyali	stainless steel V4A
Isıtma banyo çapı	400 mm
Isıtma banyo hacmi	18 l (H ₂ O) / 14 l (oil)
Buhar sıcaklık göstergesi	yes
Buhar sıcaklık göstergesi için gereken aksesuarlar	temperature sensor
Entegre vakum kontrol	yes
Zamanlayıcı	yes
Vakum program SETpressure	yes
AUTOaccurate vakum program AUTOaccurate sensör gerektirir	yes
Programlanabilir ramplar	yes
Güç sağlamak	4.600 W
Cam montajsız ağırlık	approx. 120 kg
Ekran	7" Touchpanel
Rotasyon hız derecesi	6 – 160 rpm

Temperature measurement accuracy	$\pm 1\text{ }^{\circ}\text{C}$
Aşırı ısınma kesme koruması	yes
Otomatik banyo ısıtma kontrolü	micro processor
Su banyosu nun seviye ayarı (regülasyonu)	automatically due to level sensor and refill function
Aralıklı buhar sıcaklık sensörü göstermek	0 – 200 $^{\circ}\text{C}$ (accuracy 0.1 $^{\circ}\text{C}$)
Dimensions (w/d/h)	970 x 690 x 1600 mm (2120 mm incl. Base cart)
Mak. yoğunlaşma yüzeyi	1,2 m ²